

							_	РАР	ERS										
Shade	g/m²	40	50	60	70	80	90	100	120	130	150	160	170	200	224	250	300	350	400
OLIN REGULAR																			
Absolute white			\boxtimes						\boxtimes		\boxtimes						\boxtimes		\boxtimes
High white																			
Natural white								\boxtimes			\boxtimes		\boxtimes				\boxtimes		\boxtimes
Cream																			
lvory																			
OLIN SMOOTH																			
Absolute white																	\boxtimes	\boxtimes	
High white																			
Cream																			
OLIN ROUGH																			
Absolute white																	\boxtimes		
High white																			
Cream																			
OLIN RECYCLED																			
Cream																			
		90 g with inner print 120 g																	
					62x229	229 114x162 1			110x220 114x229			162x229	1	70x170	229	x324			
			_		= I		7 F		1 ⊨					— F		F F	$\overline{}$	П	
		L			⊿		╛┖		J L							J [
OLIN REGULAR																			
Absolute white											×	3			\boxtimes				$\overline{\mathbf{X}}$
High white																			
Natural white																			
Cream											C								
lvory																			
OLIN RECYCLED																			
Cream																			
All envelopes are with s	trip.																		
zz.opoo aro mar																			
Product in stock		Non	-stock	item, cor	ntact yo	ur local	branch	for deliv	ery time	escale							v. Please e and mii		
												quantity	/.						

OLIN RECYCLED CREAM 160 g/m^2

ANTALIS O DT planche photos EN.indd 1 29/09/10 18:41



TECHNICAL INFORMATION

Description

Olin is a fully integrated high quality range of premium offset papers, available in Smooth, Regular and Rough finish, as well as Recycled. 5 shades, from Absolute White to Ivory are also available in a large range of grammages, from 40 g to 400 g.

Pulp / Raw material

OLIN is produced by an environmental friendly manufacturing process that uses pulp from well managed forests certified in accordance with the rules of the Forest Stewardship Council (FSC).

Olin Regular, Smooth and Rough are made from 100% ECF (Elementary Chlorine Free) woodpulps. Olin Recycled is made from 100% PCF (Processed Chlorine Free) woodpulps.

Applications

Corporate communication, annual reports, business cards, letterhead, purchase orders, programmes, invitations, leaflets, pharmaceutical instructions, folders, books, comics...

Certifications

- ISO 9001
- ISO 14001
- ISO 9706: permanent paper Suitable for archival use.
- NEN 2728: only for Regular from 90 to 120 g in all shades Archiving and folding standard.
- OBA Free: only for Natural white, Cream and Ivory no use of Optical Brightener Agents in the paper manufacturing process.

Preparation

• Store at room temperature (17-23°C), at a relative humidity of 50%, from 24 to 48 hours before use.

- Protect the paper against any risk of moisture during the whole process. In particular, unwrap the paper only at the last moment before printing and rewrap it immediately after the print run.
- Do not use set-off powder when printing.

Printing

- Litho offset: suitable.
- Laser printing: fully suitable with Olin Regular from 80 g to 150 g. Use appropriate inks. A4/A3 sizes available in Absolute White and Natural White.
- Pre-printing: fully suitable with Olin Regular from 80 g to 150 g. Use appropriate inks that are laser compatible.
- Screen printing: suitable.

Pre-nress

- Large printed surface: under colour-removal necessary.
- Intense full colours:
 - Black: blue support (40%) recommended
 - Colours: one or several support colours recommended.
- Screen ruling: 150 max.
- Use of the Fogra 47 (uncoated) profile is recommended, particularly when printing red tinted graphics

Finishing and conversion

- Embossing & die-stamping: all techniques can be used.
- Hot foil stamping: no precautions are necessary when using conventional foil stamping techniques. Foil blockers can recommend the best foil to suit the image and paper chosen.
- Varnishing: possible but trials to be made first.
- Lamination: not recommended.
- Scoring: starting at 135 g, scoring with counterpart.
- Cutting: it is recommended to wait 24 hours after printing.
- Ensure that the blade of the guillotine is sharp enough in order to avoid dust deposits.

ANTALIS O DT planche photos EN.indd 2 29/09/10 18:41