



## COALA DISPLAY TEXTILE

### Product Information

290 g polyester with Greyback for Roll-Up displays  
One side a special polymer coating  
High degree of whiteness.  
Highly brilliant print at lowest ink wastage.  
Block out by the B-side coating  
Specially qualified for Rollup- Systems  
Also for banner and textile architecture  
Prints great with Solvent, UV and Latex Ink  
B1 fire resistant  
Oeko tex, PVC Free

### Technical data

Product:	Coala Display Textile	Unit	Standard
Substrate	100 % Polyester		DIN 6001
Ends / Picks	23 / 17	Fd / cm	DIN 1049-2
Yarn	300 / 330	dtex / Nm	DIN ISO 2060
Weave	Plain weave		DIN ISO 9354
Grammage	290 ± 20	g/m <sup>2</sup>	DIN ISO 2286-2
Thickness	0,37 ± 0,03	mm	DIN ISO 2286-3
Tensile strength warp/weft	> 120 / 60	daM/5cm	DIN ISO 13934-1
Tear resistance warp/weft	> 40 / 50	[N]	DIN ISO 13937-1
Whiteness	≥ 120		Berger
Light fastness	≥ 5-6	Grade	DIN ISO 105-B02
Light Transmittance	0	mm	DIN 410, DIN 13363-1
Flame Retardant	B1		DIN 4102 B1 NFPA 701, CA 1237

### Standard Dimensions

950 mm x 30 m  
1030 mm x 30 m



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

